

October 20, 2004
Case No.: NL 000045 (7790/214)
Serial No.: 09/781,383
Filed: February 12, 2001
Page 18 of 23

CLAIMS APPENDIX

1. A display device, comprising:

a liquid crystal between a first substrate provided with row or selection electrodes and a second substrate provided with column or data electrodes, said row electrodes and said column electrodes overlapping to define pixels;

column drive means for driving the column electrodes in conformity with an image to be displayed; and

row drive means for driving the row electrodes which, in the operating condition, sequentially supply groups of p row electrodes with p mutually orthogonal signals,

wherein the mutually orthogonal signals are pulses obtained from at least two types of orthogonal functions having four elementary units of time, within which four elementary units of time one pulse each time has a first polarity which opposes a second polarity of the other pulses.

2. The display device of claim 1, wherein the orthogonal signals are pulses obtained from orthogonal functions having four elementary units of time, within which four elementary units of time the one pulse having the first polarity which opposes the second polarity of the other pulses each time shifts by one elementary unit of time.

October 20, 2004
Case No.: NL 000045 (7790/214)
Serial No.: 09/781,383
Filed: February 12, 2001
Page 19 of 23

3. The display device of claim 1, wherein the orthogonal signals are pulses obtained from orthogonal functions having four elementary units of time which, viewed in a time sequence, are situated one after the other.
4. The display device of claim 3, wherein at least two orthogonal signals have opposed DC contents.
5. The display device of claim 1 or 2, wherein the orthogonal signals are pulses obtained from orthogonal functions having four elementary units of time, in which the elementary units of the orthogonal functions are interwoven.
6. The display device of claim 1 or 2, wherein $p = 4$, and in that four orthogonal signals have identical DC contents and four are free from a DC voltage.
7. The display device of claim 6, wherein the DC content of 2 orthogonal signals of the orthogonal signals having an identical DC content is opposed to that of the two other orthogonal signals.
8. The display device of claim 1 or 2, wherein said row drive means inverts the orthogonal signals after each frame period.

October 20, 2004
Case No.: NL 000045 (7790/214)
Serial No.: 09/781,383
Filed: February 12, 2001
Page 20 of 23

9. A display device, comprising:
a plurality of pixels defined by an overlapping of a plurality of row electrodes and
a plurality of column electrodes; and
drive means for driving said plurality of row electrodes to sequentially supply
groups of p row electrodes with p mutually orthogonal signals,
wherein the p mutually orthogonal signals are pulses obtained from at
least two types of orthogonal functions having four elementary units of time, and
wherein, for each elementary unit of time, one pulse has a first polarity
that opposes a second polarity of the other pulses.
10. The display device of claim 9, wherein the one pulse having the first polarity
which opposes the second polarity of the other pulses is shifted among the fourth
elementary units of time.
11. The display device of claim 9, wherein the four elementary units of time viewed
in a time sequence are situated one after the other.
12. The display device of claim 9, wherein at least two orthogonal signals have
opposed DC contents.

October 20, 2004

Case No.: NL 000045 (7790/214)

Serial No.: 09/781,383

Filed: February 12, 2001

Page 21 of 23

13. The display device of claim 9, wherein the four elementary units of time are interwoven.
14. The display device of claim 9,
wherein $p = 4$; and
wherein four orthogonal signals have identical DC contents and four orthogonal signals free from a DC voltage.
15. The display device of claim 14, the DC content of 2 orthogonal signals of the orthogonal signals having an identical DC content is opposed to that of the two other orthogonal signals.
16. The display device of claim 9, wherein said row drive means inverts the orthogonal signals after each frame period.
17. The display device of claim 1,
wherein the first polarity is a negative polarity; and
wherein the second polarity is a positive polarity.
18. The display device of claim 9,
wherein the first polarity is a negative polarity; and
wherein the second polarity is a positive polarity.

October 20, 2004
Case No.: NL 000045 (7790/214)
Serial No.: 09/781,383
Filed: February 12, 2001
Page 22 of 23

EVIDENCE APPENDIX

None.

October 20, 2004

Case No.: NL 000045 (7790/214)

Serial No.: 09/781,383

Filed: February 12, 2001

Page 23 of 23

RELATED PROCEEDINGS APPENDIX

None.